

# Introducing the Ascom d83

The professional DECT handset for professional mobile workers



The new Ascom d83 DECT mobile device is quite possibly the toughest, most versatile enterprise-grade DECT handset ever made: delivering the voice quality, reliability, messaging and alarm functions demanded in modern workplaces.

## Tested to the limits

The d83 is ingress protected to IP67 standard...but we think an enterprise-grade DECT handset has to be tougher than the toughest work environments. This is why the d83 has been tested way beyond the standard free fall, temperature, chemical-resistance and endurance tests. It also features advanced speech encryption and authentication.

## Protection with productivity

The availability of three d83 versions (Talker, Messenger, Protector), means you can select the combination of alarm features that are right for your needs. All versions deliver wideband audio and noise cancelling for exceptional voice quality, plus there's an 'express' channel for mission-critical data.

## No compromise on comfort

The d83 is built to be comfortable to use throughout the longest shifts. It features a conveniently located alarm button, large color display, wired or wireless headset connectivity, multiple language and phonebook options, a carrying clip and a long-life, replaceable battery.

## Support and services, wherever you are

The d83 DECT is only part of what you get when you order an Ascom on-site communications solution. You can also take advantage of a customised after-sales support package that can include everything from remote system monitoring to prioritised device repair/replacement, training, and automatic software updates.

## Ascom d83 versions

Features	Talker	Messenger	Protector
Telephony	✓	✓	✓
Shock, vibration, drop, temperature and chemical resistant	✓	✓	✓
Centralised device management	✓	✓	✓
Central phone book	✓	✓	✓
Bluetooth 5.0 for wireless headsets	✓	✓	✓
3.5 mm contact for wired headsets	✓	✓	✓
Shared phone	✓	✓	✓
Advanced messaging including priority, confirmation, call setup, colours on display and LED	—	✓	✓
Services and shortcuts to phone calls, messaging, sending data, etc.	—	✓	✓
Location with BLE, DECT, IR and LF technologies	—	✓	✓
Push-button, man-down, no-movement and pull-cord alarms	—	—	✓

# Ascom d83 technical specifications

<p><b>BODY</b>  <b>Dimensions:</b> 150 x 64 x 23 mm  <b>Weight:</b> 175 g (6.17 oz) (incl. clip and battery)  <b>Color:</b> Handset: gray/black, Front plate: black (standard), steel grey, turquoise, green, orange  <b>Build:</b> Case: PC/ABS, Keypad: PC, Clip: PA  <b>Case:</b> Hinge type (standard), swivel type or no clip</p>	<p><b>AUDIO</b>  <b>Wideband audio:</b> Support of voice codecs G.722.2 and G.726  <b>Background noise reduction:</b> Two micro-phones and Adaptive Noise Reduction  <b>Ring signal:</b> Adjustable in 8 steps  <b>Max. sound ring signal level:</b> 100 dBA at 10 cm distance  <b>Earpiece:</b> Adjustable in 8 steps of 3dB each  <b>Loudspeaker:</b> Duplex loudspeaker</p>	<p><b>LANGUAGES</b>  <b>Menu and message languages:</b> Arabic, Czech, Danish, Dutch, English, Finnish, Flemish, French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese (Brazilian), Portuguese (European), Russian, Simplified Chinese, Slovakian, Spanish, Swedish and Turkish plus one downloadable language</p>
<p><b>DISPLAY</b>  <b>Size:</b> 40 x 50 mm (2.4 ")  <b>Type:</b> TFT  <b>Colors:</b> 262 k individual colors  <b>Screen:</b> 240 x 320 pixel LCD with white LED backlight</p>		<p><b>LOCATION<sup>1</sup> AND ALARM<sup>2</sup></b>  <b>Location types<sup>1</sup>:</b> Bluetooth Low Energy (BLE), DECT, Infrared (IR), Low Frequency (LF)  <b>Alarm types<sup>2</sup>:</b> Push button, man-down, no-movement and/or pull-cord  <b>Optional add-ons:</b> Acoustic Location Signal, post-alarm automatic emergency call</p>
<p><b>BATTERY AND CHARGING</b>  <b>Type:</b> Li-ion 3.7 V, 920 mAh  <b>Speech time:</b> 10 hrs (with Bluetooth headset and location features enabled)  <b>Stand-by time:</b> 120 hrs (with black screen saver activated and location features disabled)  <b>Charge time:</b> &lt;4 hrs  <b>Discharge/charge cycles:</b> &gt;=80% capacity after 400 full charge/discharge cycles</p>	<p><b>USER INTERFACE</b>  <b>Indicators:</b> Sound, vibrator, illuminated display and/or a multicolored LED indicates incoming call/message, 14 ring signals  <b>Button and keys:</b> Three programmable soft keys, fourway navigation key, off-hook key, on-hook and power on/off key, numerical keys, sound off key, volume up/down, alarm button, mute multifunction button and push-to-talk multifunction button</p>	<p><b>SECURITY</b>  <b>Encryption:</b> Full support of the DECT Security EN300444 feature N35 (Enhanced security) and N36 (AES/DSAA2 authentication)</p>
<p><b>CONNECTORS</b>  <b>Multipurpose:</b> Multi-purpose connector for battery charging, fast software download and configuration.  <b>Other:</b> Screw reinforced standard 3.5 mm headset connector for Peltor/3M hearing protection headset cable The 3.5 mm connector can also be used for charging with a charging cable using a Europlug</p>	<p><b>PHONEBOOKS</b>  <b>Central phonebook:</b> Unlimited number of entries, maximum 40 characters in a name and 20 digits in a number  <b>Company phonebook:</b> 1,000 entries, maximum 24 characters in a name and 24 digits in a number  <b>Local phonebook:</b> 250 entries, maximum 48 character in a name and 24 digits in a number</p>	<p><b>ENVIRONMENTAL</b>  <b>Operating temperature:</b> -10° C to +55° C (+14° F to +131° F)  <b>Storage temperature:</b> -20° C to +60° C (-4° F to +140° F)  <b>Charging temperature:</b> +5° C to +40° C (+41° F to +104° F)  <b>Enclosure protection:</b> IP67, IEC EN60529  <b>Immunity to ESD:</b> 8 kV contact discharge and 16 kV air discharge, EN61000-4-2  <b>Free fall test:</b> IEC60068-2-31, procedure 1: dropped 12 times, specification extended to 2 m. IEC60068-2-31, procedure 2: dropped 1000 times from 0.5 m  <b>Climate stress:</b> Handset exposed to rapid temperature and humidity changes  <b>Temperature range:</b> -40° C to +75° C (-40° F to +167° F)  <b>Humidity range:</b> 0% to 90%  <b>Vibration test:</b> Handset exposed to 30 Hz vibrations for a duration of 2.5 hrs  <b>Chemical stress:</b> Handset exposed to oleic acid  <b>Keypad actuation test:</b> Keys pressed 15,000 times with a force of 13 N  <b>Squeeze test:</b> Handset squeezed 1,000 times with a force of 130 N</p>
<p><b>RADIO</b>  <b>Color:</b> DECT protocol detection: Automatic detection and configuration for US DECT and EU DECT at first registration  <b>Frequency range:</b>  1880–1900 MHz: Europe, Africa, Middle East, Australia, New Zealand and parts of Asia  1900–1906 MHz: Thailand  1910–1920 MHz: Brazil  1910–1930 MHz: Latin America  1920–1930 MHz: US  <b>Modulation:</b> GFSK  <b>Channel spacing:</b> 1.728 MHz  <b>Antenna:</b> Two integral antennas for diversity  <b>Sensitivity:</b> -93 dBm  <b>Maximum:</b> 10 mW: Europe, Latin America, Brazil, 4 mW: US  <b>Bluetooth:</b> Supports Bluetooth 5.0 and profiles headset and handsfree</p>	<p><b>TELEPHONY</b>  <b>Answer call:</b> Button press or auto answer  <b>Call list storage capacity:</b> 50 calls (received, dialed and missed) with time stamp</p>	
	<p><b>MESSAGING<sup>1</sup></b>  <b>Maximum message length:</b> Up to 140 characters from handset, depending on language and system settings  <b>Storage capacity:</b> 30 received/sent messages (&gt;20,000 characters)  <b>Other:</b> Configurable beeps depending on urgency, pre-programmed messages</p>	

1. Supported on Messenger and Protector
2. Supported on Protector

Ascom UK Ltd.  
Wall Island, Birmingham Road,  
Lichfield, Staffordshire, WS14 0QP  
Phone: +44 (0)121 353 6151  
uk.info@ascom.com  
www.ascom.com/uk

